

Part Number: 1510ECH



AUDIO ANALOG 4 PAIR 24AWG, BELDFOIL, LSZH-C

Product Description

ANALOG AUDIO 4 PAIR 24AWG/0.22mm², BELDFOIL, LSZH-C

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Cca
Suitable Applications:	4-pair 24AWG halogen-free multi-core cable; For analogue audio

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D
24	7x32	TC - Tinned Copper	7x0.20 mm

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Insulation	Polyethylene	1.02 mm	0.05 mm

Color Chart

Number	Color
Pair 1 t/m 4	Red & Black

Inner Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D	Drainwire Position
Foil, bonded to jacket	Aluminum / Polyester	100 %	Stranded tinned copper	24	7x0.20 mm	Under shielding foil

InnerShield, Table Note:	Aluminum inside
--------------------------	-----------------

Inner Jacket Material

Material	Nominal Diameter
FRNC / LSZH	2.86 mm

InnerJacket, Table Note:	Jacket single element, elements are numbered 1 - 4
--------------------------	--

Outer Shield Material

Type	Material	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Foil	Aluminum/Polyester	100 %	Stranded tinned copper	7xAWG26	7x0.40 mm

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
LSZH / FRNC	8.90 mm	0.40 mm	1.00 mm

Construction and Dimensions

Cabling

Description
1 center filler + 4 pairs

Min Elongation at Breakof Jacket:	125 %
Min Tensile Strength of Jacket:	9 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Nominal Inner Shield DCR
88.5 Ohm/km	52 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
92 pF/m	180 pF/m

Inductance

Nominal Inductance
0.75 µH/m

Temperature Range

Other Temp Range:	-30 to +70 °C
-------------------	---------------

Mechanical Characteristics

Max Recommended Pulling Tension:	246 N
Min Bend Radius During Installation:	89 mm
Min Bend Radius During Operation:	133.5 mm

Standards

CPR Euroclass:	Cca-s1,d1,a1
CENELEC Compliance:	EN 50290-2-20

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2013-06-12
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color	Length
1510ECH.00500	Black	500 m
1510ECH.50500	Black	500 m
1510ECH.009999	Black	450 m

History

Update and Revision:	Revision Number: 0.134 Revision Date: 09-02-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.