

# NP2X-B-CRYSTAL

2 pole 1/4" professional phone plug, gold contacts, black metal housing with CRYSTALLIZED™ - Swarovski Elements



## Features & Benefits

- 2 pole plug PX series made with CRYSTALLIZED™ - Swarovski Elements
- Fancy, noble, valuable, attractive package - an eye catcher

## Technical Information [hide](#)

### Product

Title	NP2X-B-CRYSTAL
Connection Type	Plug
Gender	male

### Electrical

Contact resistance	depends on mating connector mΩ
Dielectric strength	1 kVdc
Insulation resistance	> 2 GΩ (initial)
Rated current per contact	depends on mating connector A
Rated voltage	< 50 V

### Mechanical

Cable O.D.	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiresize	1 mm <sup>2</sup>
Wiresize	18 AWG
Wiring	Solder contacts

### Material

Bushing	Polyacetal (POM) + PU
Contact plating	0.2 μm Au
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	made with CRYSTALLIZED™ - Swarovski Elements
Shell plating	Black chromium
Strain relief	Polyacetal (POM)

### Environmental

Standard compliance IEC 60900-11 / EIA RS-459

[Home](#) [Products](#) [About us](#) [Contact](#) [Support](#)

Solderability

Complies with IEC 68-2-20

Temperature range

-20 °C to +65 °C

Accessories

BPX-\*



BPX-L



HTXP



PXR-\*

