



Part Number: YE00820

CLASSIC ORIGINAL CLASSIC

**Product Description** EIB cable 4x0.8B PVC FS PVC

# **Technical Specifications**

## **Product Overview**

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	EIB cable for building management

# **Physical Characteristics (Overall)**

## Conductor

Stranding	Material	Cross Section	Nominal Diameter	No. of Conductors
Solid	BC - Bare Copper	0.5 mm <sup>2</sup>	0.8 mm	4
Conductor	Count:			4
Total Numb	er of Pairs:			2
Conductor S	Size:			0.50 mm <sup>2</sup>

### Insulation

P	Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
PVC - Po	olyvinyl Chloride	1.4 mm	0.05 mm	0.3 mm

## Color Chart

 Number
 Color

 Quad 1
 White & Red & Yellow & Black

#### **Outer Shield Material**

Туре	Material	Material Trade Name	Coverage [%]	Thickness of Foil	Drainwire Material	Drainwire Diameter
Таре	Aluminum/Polyester	Beldfoil®	100 %	9 µm	TC - Tinned Copper	0.4 mm

### **Outer Jacket Material**

Material	Color	Nominal Diameter	Diameter - Tolerance	Nominal Wall Thickness
PVC - Polyvinyl Chloride	Green (RAL 6017)	6.1 mm	0.3 mm	1.2 mm

## **Construction and Dimensions**

## Cabling

Description
1 quad covered with a polyester foil

## **Electrical Characteristics**

### Conductor DCR

Max. Conductor DCR 37.5 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor	
50 pF/m	
Temperature Range	
Storage Temp Range:	-30°C to +70°C
Operating Temp Range:	-20°C To +70°C
Mechanical Characteristics	
Min Bend Radius During Installation:	30.5 mm
Standards	
CPR Euroclass:	Еса
Other Specification:	KNX REG 109/7253/05
Applicable Environmental and Other Programs	
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
Flammability, LS0H, Toxicity Testing	

#### **Part Number**

## Variants

ltem #	Color	Length
YE00820.00100	Green	100 m
YE00820.001000	Green	1,000 m
YE00820.00500	Green	500 m
YE00820.K01000	Green	1,000 m
YE00820.001525	Green	1,525 m
YE00820.K0100	Green	100 m
YE00820.K01525	Green	1,525 m
YE00820.K0500	Green	500 m
YE00820=00100	Green	100 m
YE00820=001000	Green	1,000 m
YE00820=001525	Green	1,525 m
YE00820=00500	Green	500 m
YE00820=K0100	Green	100 m
YE00820=K01000	Green	1,000 m
YE00820=K01525	Green	1,525 m
YE00820=K0500	Green	500 m

# History

#### © 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.