

NOVACORD

SPEAKER 4x2.5 PVC



Oxygen Free Copper
99,9%



Flexible
construction



Pure signal
transmission



Audio cables are used in professional broadcasting systems for the transmission of analogue audio signals. Speaker cable features a strand design of 4x2.5 mm² cores pure copper strands and is extremely flexible. It is a tried-and-tested tool for stage, studio and hi-fi applications.


Pictures:



HIGHEST QUALITY - RELIABILITY - INNOVATION

Novacord

Speaker cable 4x2.5, AWG 13, PVC, IEC 60332-1



- 1 - Jacket
- 2 - Insulation
- 3 - Conductor

Structure

Conductor

Cross Sec. Area	2.5 mm ² , Ø 2.05 mm
No. of Cores	4 cores
Material	OFC
Type of conductor	Stranded
Strands	80/0.2±0.008 mm

Insulation

Material	PVC
Diameter	3.05 ±0.1 mm
Color	Black, Red

Jacket

Material	PVC
Diameter	11.2±0.2 mm
Color	Matt Black, RAL9005

Mechanical properties

Bending radius	without load	45 mm / 4xD (outer diameter)
	with load	90 mm / 8xD (outer diameter)
Max pull tension		200 N
Temperature range		-30°C to +70°C

Electrical properties

at 20 °C

DC Resistance	≤ 7 Ω/km
Insulation resistance	> 200 MΩ/km
Operating voltage	50/75V AC/DC

Speaker cable 4x2.5, AWG 13, PVC, IEC 60332-1

Standarts

Flame resistance

IEC 60332-1

Technical data

Article	Delivery length	Drum size	Weight
300DW	300 m	400/160/200	88 kg

© NOVACORD Inc. 2022 All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Novacord Inc. Although Novacord makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission

Novacord Inc. provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Novacord be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Novacord has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Novacord Inc. The information is believed to be correct at the time of issue. Novacord Inc. reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Novacord Inc.

HIGHEST QUALITY - RELIABILITY - INNOVATION

novacord.de

Novacord