


Product: [70042](#) 



AUDIO ANALOG 4 PAIR, 26AWG, LSZH

## Product Description

ANALOG AUDIO 4 PAIR, 26AWG/0.14mm<sup>2</sup>, LSZH

## Technical Specifications

### Product Overview

|                        |  |
|------------------------|--|
| Suitable Applications: | Audio snake cable used in professional studios; For the transmission of analogue signals |
|------------------------|--|

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material  | Cross Section        | Construction n x D |
|-----|-----------|---|----------------------|--------------------|
| 26  | 7x34      | BC-OFHC - Oxygen-Free Bare Copper (High Conductivity) | 0.14 mm <sup>2</sup> | 7x0.16 mm          |

|                        |   |
|------------------------|---|
| Conductor Count:       | 8 |
| Total Number of Pairs: | 4 |

#### Insulation

| Type       | Material          | Nominal Diameter | Diameter +/- Tolerance |
|------------|-------------------|------------------|------------------------|
| Insulation | PE - Polyethylene | 1.00 mm          | 0.03 mm                |

#### Color Chart

| Number       | Color       |
|--------------|-------------|
| Pair 1 t/m 4 | White & Red |

#### Inner Shield Material

| Type | Material    | Material Trade Name | Coverage [%] | Drainwire Material     | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|---------------------|--------------|------------------------|---------------|------------------------------|
| Tape | Alum / Poly | Beldfoil®           | 100%         | Stranded tinned copper | 26            | 7x0.16 mm                    |

|              |                 |
|--------------|-----------------|
| Table Notes: | Aluminum inside |
|--------------|-----------------|

#### Inner Jacket Material

| Material                                      | Nominal Diameter | Diameter +/- Tolerance |
|---|------------------|------------------------|
| LSZH - Low Smoke Zero Halogen flame retardant | 2.80 mm          | 0.10 mm                |

|              |  |
|--------------|--|
| Table Notes: | Elements are numbered for identification |
|--------------|--|

#### Outer Shield Material

| Type | Material    | Coverage [%] | Drainwire Material | Drainwire AWG | Drainwire Construction n x D |
|------|-------------|--------------|--------------------|---------------|------------------------------|
| Tape | Alum / Poly | 100%         | TC - Tinned Copper | 26            | 7x0.16 mm                    |

#### Outer Jacket Material

| Material                                      | Nominal Diameter | Nominal Wall Thickness |
|---|------------------|------------------------|
| LSZH - Low Smoke Zero Halogen flame retardant | 9.30 mm          | 1.20 mm                |

## Construction and Dimensions

### Cabling

| Description | Filler |
|-------------|--------|
|             |        |

1 filler + 4 pairs Polypropylene

## Electrical Characteristics

### Conductor DCR

#### Nominal Conductor DCR

134.0 Ohm/km

### Capacitance

#### Nom. Capacitance Conductor to Conductor

90 pF/m

### Delay

#### Nominal Velocity of Propagation (VP) [%]

66%

## Temperature Range

Other Temp Range: -30 to +70 °C

## Mechanical Characteristics

Min Bend Radius During Installation: 93 mm

Min Setting Radius: 46.5 mm

## Applicable Environmental and Other Programs

Environmental Space: Indoor

EU RoHS Compliance Date (yyyy-mm-dd): 2005-01-01

## Flammability, LS0H, Toxicity Testing

IEC Flammability: IEC 60332-1-2

LOI of Jacket: Min. 34 %

IEC 60754-1 (EN50267-1)- Halogen Amount: Zero

IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Max. Conductivity: 2.5 µS/mm

IEC 60754-2 (EN50267-2)- Halogen Acid Gas Amount - Min. pH: 4.3

## Part Number

### Variants

| Item #      | Color | Putup Type | Length | EAN           |
|-------------|-------|------------|--------|---------------|
| 70042.00100 | Black | Reel       | 100 m  | 8719605009814 |
| 70042.00500 | Black | Reel       | 500 m  | 8719605009821 |

## History

Update and Revision: Revision Number: 0.146 Revision Date: 04-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.