

## ARQIS208

### CABINET LOUDSPEAKERS

#### *Architectural Loudspeaker Cabinet*



### PRODUCT OVERVIEW

ARQIS208 is a 2-way wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 300 WRMS @ 8 ohm, 2 x 8" woofer and 1" HF Compression Driver. Its "U" shape wall bracket (included) allows for tilt adjustment. It has been specifically designed to fulfil permanent installation requirements where a perfect balance between sound performance and architectural / interior's design matching is a must.

### KEY FEATURES


- Full range, 2-way architectural loudspeaker
- 300 WRMS @ 8 ohm
- 2 x 8" low frequency woofer
- 1" high frequency compression driver (rotatable)
- Double INPUT/STACK connector, Euroblock + Speakon® type, with security attachment screws to avoid accidental disconnection
- "U" Shape wall bracket included, allowing for tilt adjustment
- 8 x M8 cabinet flying points.
- Metal safety sling included, to avoid drops in case of accidental detachment from the wall surface
- Available in black or white finish

### APPLICATIONS

- Shopping malls
- Sports centres
- Theatres / auditoriums
- Conference rooms
- A/V presentations
- Corporate rooms
- Perimeter reinforcement in clubs
- Cafés
- Restaurants
- Theme parks


POLAR DIAGRAMS

HORIZONTAL




Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	164	2.2	3.4
⋯	500.00	69	5.2	7.2
—	1.00K	25	14.1	11.5
- - -	2.00K	11	33.0	15.2
⋯	4.00K	73	4.9	6.9
—	8.00K	44	8.2	9.2

VERTICAL



Curve	Freq	BW	Q	DI
—	125.00	360	1.0	0.0
- - -	250.00	360	1.0	0.0
⋯	500.00	207	1.7	2.4
—	1.00K	127	2.8	4.5
- - -	2.00K	95	3.8	5.8
⋯	4.00K	47	7.6	8.8
—	8.00K	62	5.8	7.7

## FREQUENCY RESPONSE



## TECHNICAL DATA

<b>Ways</b>	2
<b>Impedance</b>	8Ω
<b>RMS power</b>	300 WRMS
<b>Program power</b>	600 WRMS
<b>Sensitivity</b>	96dB
<b>Sound pressure</b>	124dB
<b>Frequency response (±3dB)</b>	65Hz÷18kHz
<b>Cross-over frequency</b>	3.5kHz
<b>Dispersion (HxV)</b>	90°x60°
<b>Driver LF/MF</b>	2x8"
<b>Driver HF</b>	Compression driver 1"
<b>Connection</b>	Euroblock 2 ways + Speakon® 4 ways
<b>Dimensions (WxDxH)</b>	610x244x280mm
<b>Weight</b>	14.4kg
<b>Color</b>	Black (RAL 9005) / White (RAL 9016)