



## NYS373-\*

Phono plug, black shell, gold plated contacts, rubber boot for best antikink protection, chuck type strain relief for cable O.D. 3.5 to 6.1 mm, color coding ring

\*: 0-Black, 2-Red, 4-Yellow, 5-Green, 6-Blue, 9-White



Image gallery



Technical Information [hide](#)

<b>Product</b>	
Title	NYS373-*
<b>Electrical</b>	
Dielectric strength	0.5 kVdc
Insulation resistance	≥ 1 GΩ
Rated current	depends on mated connector
Contact resistance	depends on mated connector
<b>Mechanical</b>	
Cable O.D.	3.5 - 6.1 mm
Lifetime	> 1000 mating cycles
Wiresize	24 AWG
<b>Material</b>	
Contact plating	Au
Contacts	Brass (CuZn39Pb3)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black
Strain relief	Internal plastic chuck
Insulation	Thermoplastic

Environmental

Solderability

Complies with IEC 68-2-20

Temperature range

-25 °C to +70 °C

---

---

Data subject to change without prior notice. © 2012 NEUTRIK AG ® ALL RIGHTS RESERVED

**REAN**<sup>®</sup>  
REAN a brand of Neutrik AG