

For more Information  
please call

1-800-Belden1



## General Description:

13 AWG stranded (7x21) .089" silver-plated copper conductor, polyethylene insulation, double silver-plated copper braid shield (95% coverage), non-contaminating PVC jacket.

## Physical Characteristics (Overall)

### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	13	7x21	SPC - Silver Plated Copper	2.2606

Total Number of Conductors: 1

### Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PE - Polyethylene	7.239

### Outer Shield

Outer Shield Material:

Layer #	Type	Outer Shield Material	Coverage (%)
1	Braid	SPC - Silver Plated Copper	95.000
2	Braid	SPC - Silver Plated Copper	95.000

### Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVCNC - Polyvinyl Chloride Non-Contaminating

### Overall Cable

Overall Nominal Diameter: 10.795 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

UL Temperature Rating: 60°C

Bulk Cable Weight: 194.954 Kg/Km

Max. Recommended Pulling Tension: 1000.845 N

Min. Bend Radius/Minor Axis: 152.400 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMX

CEC/C(UL) Specification: CMX

AWM Specification: UL Style 1354

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-C-17, M17/075
RG Type:	214/U

### Flame Test

UL Flame Test:	VW-1
----------------	------

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)

50

### Nom. Inductance:

Inductance (µH/m)

0.252637

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

101.055

### Nominal Velocity of Propagation:

VP (%)

66

### Nominal Delay:

Delay (ns/m)

5.05274

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

5.5777

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

2.2967

### Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100m)

1	0.55777
10	1.80455
50	4.2653
100	6.2339
200	8.8587
400	13.4521
700	21.3265
900	24.9356
1000	26.248
4000	65.62

### Max. Power Rating:

Freq. (MHz) Rating (W)

50	1500
100	907
200	549

400	332
700	221
900	184
1000	171
4000	62

**Max. Operating Voltage - UL:**

Voltage	Description
30 V RMS	UL AWM Style 1354
300 V RMS	NEC

**Max. Operating Voltage - Non-UL:**

Voltage
3700 V RMS (MIL-Spec.)

## Notes (Overall)

**Notes:** Non-SWR swept version of RG-214.

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8268 0101000	1,000 FT	140.000 LB	BLACK	C	#13 PE DBLB PVC
8268 010500	500 FT	70.500 LB	BLACK	C	#13 PE DBLB PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 07-29-2013

© 2019 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.