

NBB75DFG

Grounded BNC chassis connector, feedthrough in nickel D-shape housing

Neutrik's BNC chassis connectors offer a true 75 Ω design for serial and digital (HD) signals. The machined brass connector body provides an extremely rugged and non-abrasive connection over long term use and is in addition recessed and therefore well protected in a D-shape housing (audio industry standard).



Features & Benefits

- Gold plated cage type center contact
- True 75 Ω design meets the stringent HD requirements
- Grounded panel mount
- Standard D-shape housing - provides flush mounting and protection from damage
- Color coding possible

New cage type contact

- Closed contact design - extremely robust
- Gold plated cage type clip - best possible shielding and lowest contact resistance



Technical Information [hide](#)

Product	
Title	NBB75DFG
Connection Type	BNC 75 Ω
Gender	female
Electrical	
Signal Type	HD, SDI, Video, AES/EBU, Composit, YUV, RGB, RGBH, RGBHV
Contact resistance	≤ 3 m Ω (inner)
Contact resistance	≤ 2 m Ω (outer)
Dielectric strength	1,5 kVdc
Impedance	75 Ω
Insulation resistance	> 5 G Ω
Rated voltage	<50 V
VSWR	≤ 1.03 / >37 dB up to 1 GHz ≤ 1.05 / >32 dB up to 2 GHz ≤ 1.08 / >28 dB up to 3 Ghz

Mechanical

Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Locking device	Bayonett
Mounting direction	Front mounting
Chassis shape	D

Material

Contacts	Brass (CuZn39Pb3), 0.2 µm AuCo (Center contact)
Insert	PTFE
Shell	Polyacetal (POM) (Insulation Shell)
Shell plating	Optalloy®
D-Shape housing	Zinc diecast (ZnAl4Cu1) gal Ni plating

Environmental

Temperature range	-30 °C to +85 °C
-------------------	------------------

Accessories

DSS-*



MFD



SCDP-*



SCDX



SCF



SCCD-W



SCD-W

