



**Part Number:** 9180

Audio Cable, #26-1pr, TC, O/A Foil, CM

## Product Description

110 Ohm, 26 AWG stranded (7x34) .018" TC conductors, Datalene® insulation, twisted pair, Beldfoil® shield (100% coverage), 26 AWG stranded TC drain wire, PVC jacket.

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
26	7x34	TC - Tinned Copper	0.019 in	1
Total Number of Conductors:			2	

#### Insulation:

Material	Material Trade Name	Nominal Diameter
FHDPE - Foam High Density Polyethylene	Datalene®	0.049 in

#### Color Chart 1:

Number	Color
1	Black & White

#### Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	Beldfoil®	100 %	TC - Tinned Copper	26	7x34 mm

#### Outerjacket 1:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.144 in

## Electrical Characteristics

### Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
37.3 Ohm/1000ft	23.1 Ohm/1000ft

### Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
13 pF/ft	26 pF/ft

### Impedance:

Nominal Characteristic Impedance
110 Ohm

### High Frequency (Nominal/Typical):

Nom. Insertion Loss
0.84 dB/100ft
1.18 dB/100ft
1.34 dB/100ft
1.54 dB/100ft
1.69 dB/100ft
1.92 dB/100ft
2.14 dB/100ft
2.4 dB/100ft
2.75 dB/100ft
3.09 dB/100ft
3.18 dB/100ft
4.2 dB/100ft

### Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.34 ns/ft	76 %

### High Freq:

Frequency [MHz]
0.38 MHz
0.77 MHz
1 MHz
1.5 MHz
2 MHz
3.1 MHz
4.1 MHz
5.6 MHz
8.2 MHz
11.3 MHz
12.3 MHz
24.6 MHz

### Current:

Max. Recommended Current [A]
1.9 Amps per conductor @ 25°C

### Inductance:

Nominal Inductance
0.23 $\mu$ H/ft

### Voltage:

UL Voltage Rating
300V RMS V

### Use

Max Recommended Pulling Tension:	10.5 lbs
----------------------------------	----------

### Safety

CSA Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading

### Temperature Range

Non-UL Temp Rating:	75°C °C
Operating Temp Range:	-40°C To +75°C °C

### Mechanical Characteristics

Min Bend Radius/Minor Axis:	1.5 in
-----------------------------	--------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
CEC/C(UL) Specification:	CMG
MII Order #39 (China RoHS):	Yes
NEC/(UL) Specification:	CMR
Other Specification:	AES/EBU
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No

## History

Notes:	For cross-connect use with 7891A (et al.) Digital Audio Snake Cables.
--------	---

## Product Variants

Part Number	Color	Put-Up Type	Length
9180	CHROME	Reel	1000 ft
9180	CHROME	Reel	305 m
9180 0601000	CHROME	Reel	1000 ft
9180	VIOLET Z4B	Reel	1000 ft
9180	VIO Z4B	Reel	305 m
9180 Z4B1000	VIOLET Z4B	Reel	1000 ft
9180			
9180			
9180			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.