

ORP8F

8 pole female chassis connector, solder contacts, 180° coding, black housing

The neutriCON connectors are designed for multipin/industrial applications in harsh and demanding environment. The very robust all metal circular connector offers easy and screwless assembly, flexible part combination and a push-pull locking mechanism.



Features & Benefits

- Contact configuration can be selected from 1 to 8 contacts.
- Easy assembly: Contact soldering in disassembled condition avoids awkward wiring of high density contacts.
- Precise and robust all metal housing.
- Push-pull self-locking system.

Technical Information [hide](#)

Product	
Title	ORP8F
Connection Type	neutriCON
Gender	female
Electrical	
Contact resistance	≤ 5 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 0.5 GΩ (after damp heat test IEC 68-2-30)
Rated current per contact	7,5 A
Rated voltage	< 50 V
Mechanical	
Cable retention	> 50 N
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Wiresize	1 mm ²
Wiresize	18 AWG
Wiring	Solder contacts
Locking device	Push-Pull
Mounting direction	Front mounting
Material	
Contact plating	0.3 μm Au hard alloy over 2 μm Ni
Contacts	Brass (CuZn35Pb2)
Insert	PBTP 15 % GR

Shell plating	Black chromium
---------------	----------------

Environmental

Flammability	UL 94 HB
--------------	----------

Protection class	IP 5X
------------------	-------

Solderability	Complies with IEC 68-2-20
---------------	---------------------------

Temperature range	-30 °C to +80 °C
-------------------	------------------
