

# NOVACORD

## SPEAKER 2x4 PVC



Oxygen Free Copper  
99,9%



Flexible  
construction





Pure signal  
transmission



Audio cables are used in professional broadcasting systems for the transmission of analogue audio signals. Speaker cable features a strand design of 2x4 mm<sup>2</sup> cores, pure copper strands, and is extremely flexible. It is a tried-and-tested tool for stage, studio, and hi-fi applications.


Pictures:



**HIGHEST QUALITY - RELIABILITY - INNOVATION**

Novacord

# Speaker cable 2x4, AWG 11, PVC, IEC 60332-1



- 1 - Jacket
- 2 - Insulation
- 3 - Conductor

## Structure

### Conductor

Cross Sec. Area	4 mm <sup>2</sup> , Ø 2.55 mm
No. of Cores	2 cores
Material	OFC
Type of conductor	Stranded

Strands 56/0.3±0.008 mm

### Insulation

Material	PVC
Diameter	3.85 ±0.1 mm
Color	Black, Red

### Jacket

Material	PVC
Diameter	9.1±0.2 mm
Color	Matt Black, RAL9005

## Mechanical properties

Bending radius	without load	37 mm / 4xD (outer diameter)
	with load	73 mm / 8xD (outer diameter)
Max pull tension		200 N
Temperature range		-30°C to +70°C

## Electrical properties

at 20 °C

DC Resistance	≤ 4.4 Ω/km
Insulation resistance	> 200 MΩ/km
Operating voltage	50/75V AC/DC

# Speaker cable 2x4, AWG 11, PVC, IEC 60332-1

## Standarts

Flame resistance

IEC 60332-1

## Technical data

Article	Delivery length	Drum size	Weight
500DW	500 m	500/250/310	86.5 kg

© NOVACORD Inc. 2022 All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Novacord Inc. Although Novacord makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission

Novacord Inc. provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Novacord be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Novacord has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Novacord Inc. The information is believed to be correct at the time of issue. Novacord Inc. reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Novacord Inc.

**HIGHEST QUALITY - RELIABILITY - INNOVATION**

novacord.de