

NAC3MPA-1

Chassis connector, power-in, 3/16" flat tab terminals, blue

The powerCON is a locking 3 conductor equipment AC connector with contacts for line, neutral and pre-mating ground contact. It replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed order to guarantee a safe power connection.




Attention: The powerCON is a connector without breaking capacity, ie the powerCON should not be connected or disconnected under load or live!

Features & Benefits

- Locking 20 A / 250 V ac appliance coupler
- 3 contacts for line, neutral and pre-mating safety ground
- Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating
- Fast and easy twist lock latching system
- Extremely robust and reliable
- Ergonomic design
- User friendly latch design for easy handling
- UL, cUL recognized components, VDE certified
- Branded with unique hologram - guarantees genuine and authentic Neutrik product

Image gallery



Technical Information [hide](#)

Product	
Title	NAC3MPA-1
Gender	male
Electrical	
Contact resistance	≤ 3 mΩ
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	> 0.1 GΩ (after damp heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rated current per contact	20 A rms
Rated voltage	250 V ac
Mechanical	
Lifetime	> 1000 mating cycles
Locking device	Quick Lock
Mounting direction	Front mounting
Chassis shape	D
Material	
Contact plating	2 μm Ag
Locking element	Steel Ck67

Contacts Bronze (CuNi1Si0.2)

Environmental

Flammability UL 94 V-0

Temperature range -30 °C to +80 °C

Accessories

CAS-DUMMY



MFD



NDL



SCDP-*



SCDR



SCL



SCD-W



NLFASTON



SCDX



SCCD-W

