



Part Number: 8460

Speaker Cable, #18-2c, TC, Unshielded, CM

Product Description

18 AWG stranded (7x26) ETP high-conductivity tinned copper conductors, PVC insulation, cabled.

Product Specifications

AG.Filter Attributes

Total Number of Conductors:	2	
-----------------------------	---	--

Technical Specifications

AG 0401

APAC Standard

MII Order #39 (China RoHS):	Yes
will Order #33 (Crima Norio).	163

Applicable Patents

Bend Radius

Min Bend Radius/Minor Axis:	1.8 in
-----------------------------	--------

CCB-Sub-Part Number

DI (V/Al).	N.
Plenum (Y/N):	No

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

EU Directive

EU Directive Compliance: EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01

North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
UL AWM Style:	UL Style 1007 (300 V 80°C)

Use

Max Recommended Pulling Tension:	50 lbs

Inductance:

Nominal Inductance

0.19 µH/ft

Conductor DCR:

Nominal Conductor DCR

5.9 Ohm/1000ft

Voltage:

UL Voltage Rating

300V RMS (UL AWM Style 1007) V

Current:

Max. Recommended Current [A]

5.2 Amps per conductor @ 25°C

Insulation:

Material	Nominal Wall Thickness	
PVC - Polyvinyl Chloride		0.02 in

Outerjacket 1:

Material	Nominal Diameter	
Unjacketed		0.18 in

Conductor:

AWG	Str	randing Materia	No. of Conducto	ors
18	7x26	High Conductivity TC - Tinned Copper		2

Outershield 1:

Material	
Unshielded	

Product Variants

Part Number	Color	Put-Up Type	Length
8460	BLACK & WHITE PAIR	Reel	1000 ft
8460	BLACK AND WHITE	Reel	305 m
8460 0631000	BLACK & WHITE PAIR	Reel	1000 ft
8460	BLACK & WHITE PAIR	Reel	5000 ft
8460 0635000	BLACK & WHITE PAIR	Reel	5000 ft
8460	BLACK AND WHITE	Reel	2000 m
8460	BLACK & WHITE PAIR	UnReel	1000 ft
8460	BLACK AND WHITE	UnReel	305 m
8460 063U1000	BLACK & WHITE PAIR	UnReel	1000 ft
8460			
8460			
8460			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden?s knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.