



## RT4MPR

4 pole TINY xlr male chassis connector, rearmountable, nickel housing, gold plated contacts, max. panel thickness: 3 mm

- Rear mountable design
- Shielded system – high noise immunity and EMI protection
- Watertight chassis connector, even in unmated condition



### Technical Information [hide](#)

<b>Product</b>	
Title	RT4MPR
<b>Electrical</b>	
Contact resistance	< 10 mΩ
Dielectric strength	> 0.5 kVdc
Insulation resistance	> 1 GΩ
Rated current per contact	< 5 A
<b>Mechanical</b>	
Lifetime	> 5000 mating cycles
Panel thickness	max. 3 mm
Wiresize	0.22 mm <sup>2</sup>
Wiresize	24 AWG
<b>Material</b>	
Contact plating	Au
Contacts	Brass (CuZn38Pb3)
Insert	PA 6.6 30 % GF
Shell	ZuAl4Cu1
Shell plating	Nickel
<b>Environmental</b>	
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +85 °C

Data subject to change without prior notice. © 2012 NEUTRIK AG ® ALL RIGHTS RESERVED

**REAN**<sup>®</sup>  
REAN a brand of Neutrik AG