

# NCJ10FI-H


3 pole XLR female receptacle with 1/4" switching stereo jack and switching ground contact, horizontal PCB mount

XLR / jack hybrid chassis connector combining 3 pole XLR receptacle and 1/4" jack.



## Features & Benefits

- Combined XLR receptacle and 1/4" phone jack
- Balanced or line inputs in one XLR shell
- Saves rack space by combining 2 connectors in one housing
- Very low conductor capacitance, therefore suitable for digital audio



## Technical Information hide

Product	
Title	NCJ10FI-H
Connection Type	Combo
Gender	female
Electrical	
Contact resistance	< 10 mΩ (XLR)
Contact resistance	< 20 mΩ (jack & switching contacts)
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	7,5 A (XLR)
Rated current per contact	7,5 A (Jack)
Rated voltage	< 50 V
Switching contacts	3
Mechanical	
Insertion force	≤ 25 N
Withdrawal force	≤ 25 N
Lifetime	> 1000 mating cycles
Panel thickness	max. 7 mm 0.27"
<a href="#">Home</a> <a href="#">Products</a> <a href="#">About us</a> <a href="#">Contact</a> <a href="#">Support</a>	

Mounting direction

Rear mounting

**Material**

Contact plating

0.2 µm Au hard alloy over 2 µm Ni

Contacts

Bronze (CuSn6)

Insert

Polyamide (PA 6.6 30 % GR)

Locking element

Steel Ck67

**Environmental**

Temperature range

-30 °C to +80 °C

**Accessories**

A-SCREW-1-8



CAS-DUMMY



NDF



SCF

