

1908A Multi-Conductor - FlexSnake® Super-Flexible, High-Performance Cable

For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (41x40) bare copper conductor, polyolefin insulation, individually shielded with double serve "French Braid" (93% coverage), TC drain wire, numbered/color-coded PVC jackets, overall Black PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | # Pairs | AWG | Stranding | Conductor Material | Dia. (mm) |
|--------------|---------|-----|-----------|--------------------|-----------|
| 16 | 8 | 24 | 41x40 | BC - Bare Copper | 0.5842 |

Total Number of Conductors: 16

Insulation

Insulation Material:

| Insulation Material | Dia. (mm) |
|---------------------|-----------|
| PO - Polyolefin | 1.016 |

Inner Shield

Inner Shield Material:

| Type | Inner Shield Material | Coverage (%) |
|--------------|-----------------------|--------------|
| French Braid | BC - Bare Copper | 95 |

Inner Shield Drain Wire AWG:

| AWG |
|-----|
| 24 |

Inner Shield Drain Wire Stranding: 19x26

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Inner Jacket

Inner Jacket Material:

| Inner Jacket Material | Nom. Dia. (mm) |
|--------------------------|----------------|
| PVC - Polyvinyl Chloride | 3.023 |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Overall Cable

Overall Cabling Color Code Chart:

| Color |
|-------|
| 7 |

Overall Nominal Diameter: 12.243 mm

1908A Multi-Conductor - FleXnake® Super-Flexible, High-Performance Cable

Pair

Pair Color Code Chart:

| Color |
|---------------|
| Red and Black |

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|----------------|
| Operating Temperature Range: | -20°C To +60°C |
| Bulk Cable Weight: | 193.466 Kg/Km |
| Max. Recommended Pulling Tension: | 1023.086 N |
| Min. Bend Radius/Minor Axis: | 127 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | No |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

| Impedance (Ohm) |
|-----------------|
| 60 |

Nom. Inductance:

| Inductance (µH/m) |
|-------------------|
| 0.59058 |

Nom. Capacitance Conductor to Conductor:

| Capacitance (pF/m) |
|--------------------|
| 85.6341 |

Nom. Capacitance Cond. to Other Conductor & Shield:

| Capacitance (pF/m) |
|--------------------|
| 155.848 |

Nominal Velocity of Propagation:

| VP (%) |
|--------|
| 66 |

Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 83.6655 |

| | |
|---|---------------|
| Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: | 23.623 Ohm/km |
|---|---------------|

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

METRIC MEASUREMENT VERSION

1908A Multi-Conductor - FleXnake® Super-Flexible, High-Performance Cable

Max. Recommended Current:

| Current |
|--------------------------------|
| 1.05 Amps per conductor @ 25°C |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|--------------|-------|-------------------|
| 1908A B591000 | 1,000 FT | 138.000 LB | BLACK, MATTE | C | 8 #24 JKTD PR PVC |
| 1908A B59250 | 250 FT | 36.000 LB | BLACK, MATTE | | 8 #24 JKTD PR PVC |
| 1908A B59500 | 500 FT | 72.500 LB | BLACK, MATTE | | 8 #24 JKTD PR PVC |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-04-2012

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.