

## Patch & Instrument Cable SC-Onyx 2025 MKII; 2 x 1 x 0,25 mm<sup>2</sup>; PVC; 8,3 x 3,8 mm; black Art. No.: 320-0101

ANALOG

OFC



### General Data

|                    |                          |
|--------------------|--------------------------|
| Article number :   | 320-0101                 |
| Name :             | SC-Onyx 2025 MKII        |
| EAN :              | 4049371003292            |
| Properties :       | Analog                   |
| Properties :       | OFC oxygen free copper   |
| Application area : | Studio / Broadcast       |
| Application area : | Installation             |
| Application :      | Patch & Instrument Cable |
| Colour :           | black                    |
| Colour detailed :  | black                    |
| BPVo-Euroclass :   | Fca                      |

### Technical Data

|  |                             |
|--|-----------------------------|
| Signal transmission :                        | asymmetrical                |
| Construction :                               | LI2YDY2x0,25mm <sup>2</sup> |
| Jacket material :                            | PVC                         |
| Number of Channels (audio) :                 | 2                           |
| Inner conductor (audio) :                    | 1                           |
| Inner conductor (audio) [mm <sup>2</sup> ] : | 0,25                        |
| Inner conductor Ø (audio) [mm] :             | 0,56                        |
| AWG (audio) :                                | 24                          |
| Shielding :                                  | Copper spiral shielding     |
| Shielding factor [%] :                       | 90                          |
| Copper strands (audio) :                     | 32                          |
| Copper strand Ø (audio) [mm] :               | 0,10                        |
| Conductor insulation material :              | PE                          |
| Weight per 1 m [g] :                         | 38                          |
| UV-resistant :                               | yes                         |
| Fire load per m [kWh] :                      | 0,23                        |
| Style variant :                              | round                       |
| Packing :                                    | 100 m spool                 |
| Temperature min. [°C] :                      | -20                         |
| Temperature max. [°C] :                      | 70                          |
| Width [mm] :                                 | 8,3                         |
| Height [mm] :                                | 3,8                         |

### Electrical Data

|   |     |
|---|-----|
| Capac. cond./shield. per 1 m (audio) [pF] : | 120 |
| Insulation resist. per 1 km [GΩ] :          | 1   |
| Insulation resist. per 1 km (audio) [GΩ] :  | 1   |
| Conductor resistance per 1 km [Ω] :         | 115 |