

Speaker Cable Elephant Robust SPM840; 8 x 4,00 mm²; PVC Ø 18,50 mm; black

Art. No.: 490-0351-840

ANALOG

OFC

**General Data**

| | |
|----------------------|-------------------------|
| Article number : | 490-0351-840 |
| Name : | Elephant Robust SPM840 |
| EAN : | 4049371020510 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Stage / live |
| Application area : | Mobile outdoor / indoor |
| Application area : | Studio / Broadcast |
| Application area : | Installation |
| Application area : | ELA 100 V |
| Application : | Speaker Cable |
| Colour : | black |
| Colour detailed : | black |
| Old article number : | 490-0251-840 |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|--|----------------------------|
| Construction : | (8LIY4,0mm ²)Y |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 18,50 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 8 |
| Inner conductor (audio) [mm ²] : | 4,00 |
| Inner conductor Ø (audio) [mm] : | 2,26 |
| AWG (audio) : | 11 |
| Copper strands (audio) : | 128 |
| Copper strand Ø (audio) [mm] : | 0,20 |
| Conductor insulation Ø [mm] : | 3,75 |
| Weight per 1 m [g] : | 570 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 2,25 |
| Style variant : | round |
| Packing : | bulk stock |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 18,5 |
| Height [mm] : | 18,5 |

Electrical Data

| | |
|--|-------|
| Insulation resist. per 1 km [GΩ] : | 0,005 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,005 |
| Conductor resistance per 1 km [Ω] : | 4,5 |
| Test voltage [V] : | 2000 |