

Part Number: 1406B

RGB Video, High Flex, #26-3 Coax Stranded BC



Product Description

RGB Video Coax, 3-26 AWG stranded bare copper conductors, foam HDPE insulation, Duofoil® +95% tinned copper braid shield, inner PVC jackets, flexible PVC jacket

Technical Specifications

Construction and Dimensions

Conductor:

AWG	Stranding	Material	Nominal Diameter	No. of Coax
26	7x34	BC - Bare Copper	0.019 in	3
Total Number of Conductors:			3	

Insulation:

Material	Nominal Diameter
FHDPE - Foam High Density Polyethylene	0.089 in

Color Chart 3:

Number	Color
1	Red
2	Green
3	Blue

Innershield:

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum Foil-Polyester Tape-Aluminum Foil	Duofoil®	100 %
Braid	2	TC - Tinned Copper		95 %

Innerjacket:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.146 in

Outershield 1:

Material
Unshielded

Outerjacket 1:

Material	Nominal Diameter	Separator Material
PVC - Polyvinyl Chloride	0.388 in	Polyester Tape

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Inner Shield DCR
41.5 Ohm/1000ft	8.6 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Shield
17.3 pF/ft

Sweep Testing:	100% sweep tested 10 MHz to 40 MHz
----------------	------------------------------------

Impedance:

Nominal Characteristic Impedance
75 Ohm

High Frequency (Nominal/Typical):

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.6 dB/100ft
5 MHz	1.3 dB/100ft
10 MHz	1.8 dB/100ft
30 MHz	3.1 dB/100ft
50 MHz	3.9 dB/100ft
100 MHz	5.4 dB/100ft
200 MHz	7.5 dB/100ft
400 MHz	10.4 dB/100ft
700 MHz	13.5 dB/100ft
900 MHz	15.2 dB/100ft
1000 MHz	15.9 dB/100ft

Delay:

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.3 ns/ft	78 %

High Freq:

Min. RL (Return Loss) [dB]
25 dB

Voltage:

Non-UL Voltage Rating
300V RMS

Use

Max Recommended Pulling Tension:	103 lbs
----------------------------------	---------

Temperature Range

Non-UL Temp Rating:	60°C °C
Operating Temp Range:	-40°C To +60°C °C

Mechanical Characteristics

Min Bend Radius/Minor Axis:	4 in
-----------------------------	------

Part Number

Plenum (Y/N):	No
---------------	----

Standards

CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	SMPTE
RG Type:	Mini 59/U
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No

Product Variants

Part Number	Color	Put-Up Type	Length
1406B	BLACK, VIVID MATTE	Reel	1000 ft
1406B	MATTE VIVID BLACK	Reel	305 m
1406B J5C1000	BLACK, VIVID MATTE	Reel	1000 ft
1406B			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.