

NC3MAAH-1

3 pole male XLR receptacle, grounding: mating connector shell to pin1 and front panel, horizontal PCB mount

Most cost-effective round plastic body XLR PCB mount panel connector. Front panel cutout and PCB layout 100% compatible to A series. "Tulip" type contact design with high contact pressure for highest durability. Flammability rating UL94HB. UL recognized component.



Features & Benefits

- Most cost-effective series
- "Tulip" type contact design with high contact pressure for highest durability
- Selective gold plated contact and PCB termination area for best conductivity and solderability

Technical Information [hide](#)

Product	
Title	NC3MAAH-1
Connection Type	XLR
Gender	male
Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 6 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	6 A
Rated voltage	< 50 V
Grounding Options	Pin 1 connected direct to front panel and connector shell, no separate ground contact
Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	Rear mounting
Chassis shape	A
Mounting	A-Screw
Material	
Contacts	Brass (CuZn35Pb2)

Shell

Polyacetal (POM), Polyamide (PA 6.6 30 % GR)

Environmental

Approvals

UL

Flammability

UL 94 HB

Standard compliance

IEC 61076-2-103

Protection class

IP 40

Solderability

Complies with IEC 68-2-20

Temperature range

-30 °C to +80 °C

Accessories

A-SCREW-1-8



CAS-DUMMY



NDF



SCF

