

Patch & Microphone Cable SC-Goblin; 2 x 0,14 mm²; PVC Ø 4,60 mm; white

Art. No.: 200-0350

ANALOG

OFC



General Data

Article number :	200-0350
Name :	SC-Goblin
EAN :	4049371050913
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Patch & Microphone Cable
Colour :	white
Colour detailed :	white
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,14mm ²)(ST)DY
Jacket material :	PVC
Jacket Ø [mm] :	4,60
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,14
Inner conductor Ø (audio) [mm] :	0,42
AWG (audio) :	26
Shielding :	Copper spiral sleeve tin-plated + metallic fleece
Shielding factor [%] :	100
Copper strands (audio) :	18
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,05
Weight per 1 m [g] :	27
Fire load per m [kWh] :	0,1
Style variant :	round
Packing :	100 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	4,6
Height [mm] :	4,6

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	65
Capac. cond./shield. per 1 m (audio) [pF] :	120
Insulation resist. per 1 km [GΩ] :	0,2
Insulation resist. per 1 km (audio) [GΩ] :	0,2

Conductor resistance per 1 km [Ω] :	140
-------------------------------------	-----

Shield. resistance per 1 km [Ω] :	30
-----------------------------------	----