



Part Number: 8477

Audio/Control/Instrumentation, (1 pr) 12 AWG (65X30) TC,
PVC/PVC

Product Description

One 12 AWG pair stranded (65x30) tinned copper conductors, twisted pair, PVC insulation, PVC jacket.

Product Specifications

AG.Filter Attributes

Total Number of Conductors:	2
-----------------------------	---

Technical Specifications

AG_0401

UL Flammability:	UL1666 Vertical Shaft
------------------	-----------------------

APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Applicable Patents

Patent:	http://www.belden.com/p
---------	---------------------------------------------------------------

Bend Radius

Min Bend Radius/Minor Axis:	4 in
-----------------------------	------

CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
--------------------------	-------------------------------

EU CE Mark:	Yes
-------------	-----

North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

NEC/(UL) Specification:	CL3R
-------------------------	------

UL AWM Style:	UL Style 2587 (600 V 90°C)
---------------	----------------------------

Unused Attributes

Notes:	See NEC Guidelines for applicable CL3 voltage ratings.
--------	--------------------------------------------------------

Use

Max Recommended Pulling Tension:	150 lbs
----------------------------------	---------

Inductance:

Nominal Inductance

0.18 μ H/ft

Conductor DCR:

Nominal Conductor DCR

1.8 Ohm/1000ft

Color Chart 1:

Number	Color
1	Black & White

Voltage:

UL Description	UL Voltage Rating
CL3R	300 V RMS V
UL AWM Style 2587	600 V RMS

Current:**Max. Recommended Current [A]**

13 Amps per conductor @ 25°C

Capacitance:**Nom. Capacitance Conductor to Conductor**

35 pF/ft

Insulation:**Material** **Nominal Wall Thickness**

PVC - Polyvinyl Chloride 0.033 in

Outerjacket 1:**Material** **Nominal Diameter** **Nominal Wall Thickness**

PVC - Polyvinyl Chloride 0.386 in 0.035 in

Conductor:**AWG** **Stranding** **Material** **No. of Pairs**

12 65x30 TC - Tinned Copper 1

Outershield 1:**Material**

Unshielded

Product Variants

Part Number	Color	Put-Up Type	Length
8477			
8477	CHROME	Reel	305 m
8477 0601000	CHROME	Reel	1000 ft
8477			
8477 0605000	CHROME	Reel	5000 ft
8477			
8477	CHROME	Reel	152 m
8477 060500	CHROME	Reel	500 ft
8477	CHROME	Reel	305 m
8477			
8477	CHROME	UnReel	152 m
8477 060U500	CHROME	UnReel	500 ft
8477			
8477			
8477			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.