

NL4MP-ST

4 pole chassis connector, black D-size flange, countersunk thru holes, screw termination. This chassis connector is not airtight.

The speakON panel mount connectors are the standard chassis connectors for loudspeaker / amplifier interconnections. They feature a unique metal locking system, making contact only once fully locked. The speakON receptacles are robust, versatile and easy to terminate.



Features & Benefits

- Current rating 30 A rms
- Glass reinforced materials make it extremely robust and dependable
- Precise keyway for secure mating
- Accurate twist lock latching system
- Metal insert in locking area
- Branded with unique hologram - guarantees genuine and authentic Neutrik product

Technical Information [hide](#)

Product	
Title	NL4MP-ST
Connection Type	speakON
Gender	male
Electrical	
Contact resistance	≤ 3 mΩ (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 GΩ (after dampheat)
Rated current per contact	30 A rms continuous
Rated current per contact	40 A audiosignal, duty cycle 50 %
Rated voltage	250 V (Insulation)
Attention	speakON is NOT to be used as an AC mains or power supply connector!
Mechanical	
Lifetime	> 5000 mating cycles
Wiresize	4 mm ²
Wiresize	12 AWG
Wiring	screw terminals
Locking device	Quick Lock
Chassis shape	D
Layout	standard hole position, thru holes
Material	

Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6 30 % GR) black
Environmental	
Flammability	UL 94 HB
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

Accessories

CAS-DUMMY



MFD



NDL



SCDP-*



SCDR



SCDX



SCL



SCCD-W



SCD-W

