

**Speaker Cable Meridian Mobile SP215; 2 x 1,50 mm<sup>2</sup>; PVC Ø 6,80 mm; white, without imprint****Art. No.: 415-0050NE**

ANALOG

OFC

**General Data**

Article number :	415-0050NE
Name :	Meridian Mobile SP215
EAN :	4049371217804
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	white
Colour detailed :	white, without imprint
BPVo-Euroclass :	Fca

**Technical Data**

Construction :	(2LIY1,50mm <sup>2</sup> )Y
Jacket material :	PVC
Jacket Ø [mm] :	6,80
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	1,50
Inner conductor Ø (audio) [mm] :	1,38
AWG (audio) :	16
Copper strands (audio) :	84
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation Ø [mm] :	2,62
Weight per 1 m [g] :	78
UV-resistant :	yes
Fire load per m [kWh] :	0,28
Style variant :	round
Packing :	500 m spool
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	6,8
Height [mm] :	6,8

**Electrical Data**

Capac. cond./cond. per 1 m (audio) [pF] :	150
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	13